


Roulement à rouleaux NA4912-JTEKT - NA4912-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na4912-jtekt>

Machined ring needle roller bearings ————— Koyo
F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	C _r	C ₁₀	Oil lub.	Grease lub.	Without inner ring	With inner ring
68	60	85	25	—	1	45.8	93.3	9 900	—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		With inner ring	d _a max.	D _a max.	r _a max.	Without inner ring	With inner ring			
		NA4912	65	80	1	0.310	0.459	IRM00825		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483733
Diam. intérieur	60 mm
Diam. extérieur	85 mm
Épaisseur	25 mm
Poids	459 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE