


## Roulement à rouleaux NA5920-JTEKT - NA5920-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na5920-jtekt>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	$d$	$D$	$B$	$B_r$	$C_r$	$C_{10}$	Oil lub.	Without inner ring		
115	100	140	54	—	189.0	418.0	4 000	—		
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		With inner ring	$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring			
		NA5920	106.5	133.5	1	1.49	2.53	IRM10011554		

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952484242
Diam. intérieur	100 mm
Diam. extérieur	140 mm
Épaisseur	54 mm
Poids	2530 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE