


Roulement à rouleaux NA5924-JTEKT - NA5924-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na5924-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm
With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-----|--------------------------|----------------|----------------|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | B _i | C _r | C ₁₀ | Oil lub. | Without inner ring | |
| 135 | 120 | 165 | 60 | — | 244.0 | 564.0 | 3 400 | — | |
| | | Mounting dimensions (mm) | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | d _i | D _o | r _a | Without inner ring | With inner ring | | | |
| NA5924 | | 126.5 | 156.5 | 1 | 2.43 | 3.80 | IRM12013560 | | |

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952484327 |
| Diam. intérieur | 120 mm |
| Diam. extérieur | 165 mm |
| Épaisseur | 60 mm |
| Poids | 3800 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE