


Roulement à rouleaux NA5928-JTEKT - NA5928-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na5928-jtekt>

Machined ring needle roller bearings Koyo
F_W 29 – 37 mm
With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|-----|-----|----|-------------------------|-----------------|--|--------------------|-------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | | |
| 160 | 140 | 190 | 67 | 283.0 | 696.0 | 2 800 | — | | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA5928 | | | | 148 | 182 | 1.5 | 3.02 | 5.42 | IRM14016067 |

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952484402 |
| Diam. intérieur | 140 mm |
| Diam. extérieur | 190 mm |
| Épaisseur | 67 mm |
| Poids | 5420 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE