

## Douille à aiguilles BAM1016-IKO - BAM1016-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1016-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	<b>BAM 1016</b>	18.4	—	—	
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring		
F <sub>w</sub>	D	C	b <sub>2</sub> Max.	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm	IRB 716	
15.875 $\frac{1}{4}$	20.638 $\frac{3}{4}$	25.40(1.000)	1.3	15.875 Max. Min.	15.864 Max. Min.	20.650	20.629	12 300	20 800	25 000

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172927
Diam. intérieur	15.88 mm
Diam. extérieur	20.64 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE