


Douille à aiguilles BAM1312-IKO - BAM1312-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1312-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number																
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g								
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 1312	23.5	—	—						
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	f_2	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	N	N	rpm	IRB 912		
20.638	26.988	19.051	1.3	20.638	20.625	27.000	26.979	12 400	19 000	19 000	19 000	19 000	19 000	IRB 912			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173078
Diam. intérieur	20.64 mm
Diam. intérieur	13/16" inch
Diam. extérieur	26.99 mm
Diam. extérieur	1 1/16" inch
Epaisseur	19.05 mm
Epaisseur	3/4" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE