


## Douille à aiguilles BAM1412-IKO - BAM1412-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1412-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	<b>BAM 1412</b>	26	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	r <sub>2</sub> Max.	Shaft dia. h6 Max.	Housing bore dia. J7 Min.	h6 Max.	h6 Min.	N	N	rpm	IRB 1012
22.225	28.575	19.05	0.750	22.225	22.212	28.587	28.566	12 800	20 400	18 000	

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173139
Diam. intérieur	22.23 mm
Diam. intérieur	7/8" inch
Diam. extérieur	28.58 mm
Diam. extérieur	1 1/8" inch
Epaisseur	19.05 mm
Epaisseur	3/4" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE