


## Douille à aiguilles BAM1418-IKO - BAM1418-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1418-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
22.225 (7/8)	—	—	—	—	—	—	—	—	—	—	<b>BAM 1418</b>	37	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h6	Housing bore dia. J7	Max.	Min.					N
22.225	28.575	28.58(1.125)	2.8	22.225	22.212	28.587	28.566	19 900	35 600	18 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173160
Diam. intérieur	22.23 mm
Diam. extérieur	28.58 mm
Épaisseur	28.58 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE