


## Douille à aiguilles BAM1510-IKO - BAM1510-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1510-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
23.812 ( $\frac{9}{4}$ )	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)	
$F_w$	$D$	$C$	$t_1$ Max.	Shaft dia. $\phi_s$ Max.   Min.	Housing bore dia. $\phi_H$ Max.   Min.	$C$ N	$C_0$ N	$C$ N	$C_0$ N	rpm	Assembled inner ring		
23.812   $\frac{9}{4}$	30.162   $1\frac{1}{8}$	15.88   $\frac{5}{8}$	2.8	23.812   23.799	30.176   30.151	11 000	17 100	16 000	16 000	16 000	IRB 1110		

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173207
Diam. intérieur	23.81 mm
Diam. extérieur	30.16 mm
Épaisseur	15.88 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE