

## Douille à aiguilles BAM186-IKO - BAM186-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam186-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Closed end	Mass (Ref.) g	
28.575 (1 1/8)	—	—	—	—	—	—	<b>BAM 186</b>	18.1	—	—

  

Boundary dimensions mm (inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C <sub>0</sub>	rpm	
28.575 (1 1/8)	34.925 (1 3/8)	9.52 (3/8)	28.575	28.562	34.939	34.914	6 330	8 910	13 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173368
Diam. intérieur	28.58 mm
Diam. extérieur	34.93 mm
Épaisseur	9.52 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE