


Douille à aiguilles BAM1910-IKO - BAM1910-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam1910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
30.162 (1 1/8)	—	—	—	—	—	—	—	BAM 1910	37.5	—	—
Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t₁</i> Max	Shaft dia. <i>h₈</i> Max	Housing bore dia. <i>H7</i> Max	<i>J₇</i> Min	N	N	rpm		
30.162 (1 1/8)	38.100 (1 1/2)	15.88 (5/8)	2.8	30.162 (30.146)	38.114 (38.089)	15 000	22 500	12 000	—		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173382
Diam. intérieur	30.16 mm
Diam. extérieur	38.1 mm
Épaisseur	15.88 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE