


## Douille à aiguilles BAM710-IKO - BAM710-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam710-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
11.112 ( $\frac{7}{16}$ )	—	—	—	—	—	—	—	<b>BAM 710</b>	8.5	—	—
Boundary dimensions		mm (inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	$b_2$	Shaft dia. $h_8$	Housing bore dia. $J_7$	Max.	Min.	$C$	$C_0$	rpm	
11.112 ( $\frac{7}{16}$ )	15.875 ( $\frac{5}{8}$ )	15.88 (0.625)	1	11.112	11.101	15.885	15.867	6 020	7 550	35 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173528
Diam. intérieur	11.11 mm
Diam. extérieur	15.88 mm
Épaisseur	15.88 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE