


Douille à aiguilles BAM77-IKO - BAM77-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam77-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
11.112 ($\frac{7}{16}$)	—	—	—	—	—	BAM 77	6.2	—	—
Boundary dimensions mm (inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	h_8 Max.	J_7 Min.	C	C_0	rpm	—	
11.112 ($\frac{7}{16}$)	15.875 ($\frac{5}{8}$)	11.131 (438)	11.112	11.101	15.885	15.867	4 150	4 680	35 000

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173542
Diam. intérieur	11.11 mm
Diam. extérieur	15.88 mm
Épaisseur	11.13 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE