


Douille à aiguilles BAM812-IKO - BAM812-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/bam812-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
12.700 ($\frac{1}{2}$)	—	—	—	—	—	BAM 812	—	11.3	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	Shaft dia. h_8	Housing bore dia. J_7	Max.	Min.	C	C_0	rpm		
12.700 ($\frac{1}{2}$)	17.462 ($\frac{5}{8}$)	19.05 (750)	1	12.700	12.689	17.472	17.454	7 840	11 000	30 000	IRB 58

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173573
Diam. intérieur	12.7 mm
Diam. extérieur	17.46 mm
Épaisseur	19.05 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE