

Roulement conique 32938-SKF - 32938-SKF

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32938-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Désignation
d	D	T	C	C ₀	Vitesse de référence	Vitesse limite	Roulement SKF Explorer
190	260	45	358	765	1600	2400	32938

Technical drawing showing dimensions and calculation coefficients for the tapered roller bearing 32938-SKF. The drawing includes the following dimensions: d = 190 mm, D = 260 mm, T = 45 mm, C = 34 mm, r₁ = 2.5 mm, r₂ = 2.5 mm, r₃ = 2 mm, r₄ = 2.5 mm, r₅ = 2.5 mm, r₆ = 2.5 mm, r₇ = 2.5 mm, r₈ = 2.5 mm, r₉ = 2.5 mm, r₁₀ = 2.5 mm, r₁₁ = 2.5 mm, r₁₂ = 2.5 mm, r₁₃ = 2.5 mm, r₁₄ = 2.5 mm, r₁₅ = 2.5 mm, r₁₆ = 2.5 mm, r₁₇ = 2.5 mm, r₁₈ = 2.5 mm, r₁₉ = 2.5 mm, r₂₀ = 2.5 mm, r₂₁ = 2.5 mm, r₂₂ = 2.5 mm, r₂₃ = 2.5 mm, r₂₄ = 2.5 mm, r₂₅ = 2.5 mm, r₂₆ = 2.5 mm, r₂₇ = 2.5 mm, r₂₈ = 2.5 mm, r₂₉ = 2.5 mm, r₃₀ = 2.5 mm, r₃₁ = 2.5 mm, r₃₂ = 2.5 mm, r₃₃ = 2.5 mm, r₃₄ = 2.5 mm, r₃₅ = 2.5 mm, r₃₆ = 2.5 mm, r₃₇ = 2.5 mm, r₃₈ = 2.5 mm, r₃₉ = 2.5 mm, r₄₀ = 2.5 mm, r₄₁ = 2.5 mm, r₄₂ = 2.5 mm, r₄₃ = 2.5 mm, r₄₄ = 2.5 mm, r₄₅ = 2.5 mm, r₄₆ = 2.5 mm, r₄₇ = 2.5 mm, r₄₈ = 2.5 mm, r₄₉ = 2.5 mm, r₅₀ = 2.5 mm, r₅₁ = 2.5 mm, r₅₂ = 2.5 mm, r₅₃ = 2.5 mm, r₅₄ = 2.5 mm, r₅₅ = 2.5 mm, r₅₆ = 2.5 mm, r₅₇ = 2.5 mm, r₅₈ = 2.5 mm, r₅₉ = 2.5 mm, r₆₀ = 2.5 mm, r₆₁ = 2.5 mm, r₆₂ = 2.5 mm, r₆₃ = 2.5 mm, r₆₄ = 2.5 mm, r₆₅ = 2.5 mm, r₆₆ = 2.5 mm, r₆₇ = 2.5 mm, r₆₈ = 2.5 mm, r₆₉ = 2.5 mm, r₇₀ = 2.5 mm, r₇₁ = 2.5 mm, r₇₂ = 2.5 mm, r₇₃ = 2.5 mm, r₇₄ = 2.5 mm, r₇₅ = 2.5 mm, r₇₆ = 2.5 mm, r₇₇ = 2.5 mm, r₇₈ = 2.5 mm, r₇₉ = 2.5 mm, r₈₀ = 2.5 mm, r₈₁ = 2.5 mm, r₈₂ = 2.5 mm, r₈₃ = 2.5 mm, r₈₄ = 2.5 mm, r₈₅ = 2.5 mm, r₈₆ = 2.5 mm, r₈₇ = 2.5 mm, r₈₈ = 2.5 mm, r₈₉ = 2.5 mm, r₉₀ = 2.5 mm, r₉₁ = 2.5 mm, r₉₂ = 2.5 mm, r₉₃ = 2.5 mm, r₉₄ = 2.5 mm, r₉₅ = 2.5 mm, r₉₆ = 2.5 mm, r₉₇ = 2.5 mm, r₉₈ = 2.5 mm, r₉₉ = 2.5 mm, r₁₀₀ = 2.5 mm. The drawing also shows the calculation coefficients: Y₀ = 0.48, Y₁ = 1.25, Y₂ = 0.7.

CARACTÉRISTIQUES PRODUIT

Marque	SKF
N° Ean13	7316577120779
Diam. intérieur	190 mm
Diam. extérieur	260 mm
Épaisseur	45 mm
Poids	7010 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE