


## Roulement à rouleaux NUP213-ECJ-SKF - NUP213-ECJ-SKF

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nup213-ecj-skf>

Dimensions d'encadrement			Charges de base		Désignation		Bague d'épaulement	
d	D	B	C	C <sub>0</sub>	* Roulement SKF Explorer	Designation		
mm			kN					
65	120	23	122	118	NUP 213 ECJ	-		



Technical drawing showing the bearing's dimensions and internal structure. Dimensions include: d = 65 mm, D = 120 mm, B = 23 mm, r = 0.5 mm, r<sub>1</sub> = 1.5 mm, r<sub>2</sub> = 1.5 mm, r<sub>3</sub> = 1.5 mm, r<sub>4</sub> = 1.5 mm, r<sub>5</sub> = 1.5 mm, r<sub>6</sub> = 1.5 mm, r<sub>7</sub> = 1.5 mm, r<sub>8</sub> = 1.5 mm, r<sub>9</sub> = 1.5 mm, r<sub>10</sub> = 1.5 mm, r<sub>11</sub> = 1.5 mm, r<sub>12</sub> = 1.5 mm, r<sub>13</sub> = 1.5 mm, r<sub>14</sub> = 1.5 mm, r<sub>15</sub> = 1.5 mm, r<sub>16</sub> = 1.5 mm, r<sub>17</sub> = 1.5 mm, r<sub>18</sub> = 1.5 mm, r<sub>19</sub> = 1.5 mm, r<sub>20</sub> = 1.5 mm, r<sub>21</sub> = 1.5 mm, r<sub>22</sub> = 1.5 mm, r<sub>23</sub> = 1.5 mm, r<sub>24</sub> = 1.5 mm, r<sub>25</sub> = 1.5 mm, r<sub>26</sub> = 1.5 mm, r<sub>27</sub> = 1.5 mm, r<sub>28</sub> = 1.5 mm, r<sub>29</sub> = 1.5 mm, r<sub>30</sub> = 1.5 mm, r<sub>31</sub> = 1.5 mm, r<sub>32</sub> = 1.5 mm, r<sub>33</sub> = 1.5 mm, r<sub>34</sub> = 1.5 mm, r<sub>35</sub> = 1.5 mm, r<sub>36</sub> = 1.5 mm, r<sub>37</sub> = 1.5 mm, r<sub>38</sub> = 1.5 mm, r<sub>39</sub> = 1.5 mm, r<sub>40</sub> = 1.5 mm, r<sub>41</sub> = 1.5 mm, r<sub>42</sub> = 1.5 mm, r<sub>43</sub> = 1.5 mm, r<sub>44</sub> = 1.5 mm, r<sub>45</sub> = 1.5 mm, r<sub>46</sub> = 1.5 mm, r<sub>47</sub> = 1.5 mm, r<sub>48</sub> = 1.5 mm, r<sub>49</sub> = 1.5 mm, r<sub>50</sub> = 1.5 mm, r<sub>51</sub> = 1.5 mm, r<sub>52</sub> = 1.5 mm, r<sub>53</sub> = 1.5 mm, r<sub>54</sub> = 1.5 mm, r<sub>55</sub> = 1.5 mm, r<sub>56</sub> = 1.5 mm, r<sub>57</sub> = 1.5 mm, r<sub>58</sub> = 1.5 mm, r<sub>59</sub> = 1.5 mm, r<sub>60</sub> = 1.5 mm, r<sub>61</sub> = 1.5 mm, r<sub>62</sub> = 1.5 mm, r<sub>63</sub> = 1.5 mm, r<sub>64</sub> = 1.5 mm, r<sub>65</sub> = 1.5 mm, r<sub>66</sub> = 1.5 mm, r<sub>67</sub> = 1.5 mm, r<sub>68</sub> = 1.5 mm, r<sub>69</sub> = 1.5 mm, r<sub>70</sub> = 1.5 mm, r<sub>71</sub> = 1.5 mm, r<sub>72</sub> = 1.5 mm, r<sub>73</sub> = 1.5 mm, r<sub>74</sub> = 1.5 mm, r<sub>75</sub> = 1.5 mm, r<sub>76</sub> = 1.5 mm, r<sub>77</sub> = 1.5 mm, r<sub>78</sub> = 1.5 mm, r<sub>79</sub> = 1.5 mm, r<sub>80</sub> = 1.5 mm, r<sub>81</sub> = 1.5 mm, r<sub>82</sub> = 1.5 mm, r<sub>83</sub> = 1.5 mm, r<sub>84</sub> = 1.5 mm, r<sub>85</sub> = 1.5 mm, r<sub>86</sub> = 1.5 mm, r<sub>87</sub> = 1.5 mm, r<sub>88</sub> = 1.5 mm, r<sub>89</sub> = 1.5 mm, r<sub>90</sub> = 1.5 mm, r<sub>91</sub> = 1.5 mm, r<sub>92</sub> = 1.5 mm, r<sub>93</sub> = 1.5 mm, r<sub>94</sub> = 1.5 mm, r<sub>95</sub> = 1.5 mm, r<sub>96</sub> = 1.5 mm, r<sub>97</sub> = 1.5 mm, r<sub>98</sub> = 1.5 mm, r<sub>99</sub> = 1.5 mm, r<sub>100</sub> = 1.5 mm.

### CARACTÉRISTIQUES PRODUIT

Marque	SKF
N° Ean13	7316570733914
Diam. intérieur	65 mm
Diam. extérieur	120 mm
Epaisseur	23 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE