


## Roulement conique 09074-09194S-TIMKEN - 09074-09194S-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/09074-09194s-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
19.050 0.7500	52.883 2.0820	20.241 0.7969	42600 9630	2.37	2.26	11100 2500	9950 1140	2.20	49000 9300	09074 09194-S

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Cr. μm	Min Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
20.241 0.8000	14.684 0.5781	-0.1 -0.36	1.5 0.06	24.0 0.94	26.8 1.02	3.3 0.13	46.5 1.83	42.0 1.65	2.2 0.09	0.7 0.03	0.0	4.0	0.0402	0.21 0.47

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952295992
Diam. intérieur	19.05 mm
Diam. extérieur	52.88 mm
Épaisseur	20.24 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE