


## Roulement conique 1774-1729X-TIMKEN - 1774-1729X-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/1774-1729x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Factor <sup>(3)</sup> Y	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(3)</sup> K	Static C <sub>0</sub>	Inner	Outer
mm	mm	mm	N			N		N		
19.004 0.7482	56.906 2.2400	19.368 0.7625	45400 16200	1.31	1.55	11900 2850	4200 1200	1.55	45300 16200	1774 1729X

Bearing Dimensions										Geometry Factors			Bearing Weight
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
Width B	Width C	ER Cr. μm	Min Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>				G <sub>1</sub>
19.007 0.7490	19.075 0.7509	-6.9 -0.27	1.5 0.06	25.0 0.98	27.0 1.06	1.5 0.06	51.0 2.01	49.0 1.93	* *	10.6	5.4	0.0521	0.26 0.59

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952296562
Diam. intérieur	19 mm
Diam. extérieur	56.9 mm
Épaisseur	19.37 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE