


Rondelle de butée WS6085-IKO - WS6085-IKO

<https://www.123roulement.com/accessoire/rondelle/rondelle-butee/ws6085-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings



Shaft dia. mm	Identification number						
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washer	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
60	NTB 6085	38.5	AS 6085	22	WS 6085	GS 6085	105

d	D	D _w	s	B	Boundary dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	
					r _s min	C _i				N
60	85	3	1	4.75	1	86	82	38 200	219 000	3 500

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952299266
Diam. intérieur	60 mm
Diam. extérieur	85 mm
Épaisseur	4.75 mm
Matière	ACIER
Poids	100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE