


## Roulement conique 4C-6-TIMKEN - 4C-6-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/4c-6-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number			
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> e	Factor <sup>3)</sup> Y	Dynamic <sup>1)</sup> C <sub>02</sub>	Factor <sup>3)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N		N			
17.462	44.456	12.700	20500	1.40	1.25	5250	4318	1.22	39000	4C	6
0.6875	1.7500	0.5000	4530			1190	909		8640		

Bearing Dimensions										Geometry Factors			Bearing Weight
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
Width B	Width C	ER Co. μm	Min. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	Max. Housing Fillet Radius r <sub>2</sub>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>1)</sup>				A <sub>2</sub> <sup>1)</sup>
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
11.900	9.525	-1.8	1.5	22.8	24.5	1.5	41.8	38.0	0.8	1.6			
0.4680	0.3750	-0.07	0.08	0.87	0.96	0.08	1.61	1.50	0.03	0.07			
									4.6	2.6	0.0406	0.09	0.21

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952309637
Diam. intérieur	17.46 mm
Diam. extérieur	44.45 mm
Épaisseur	12.7 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE