

## Roulement conique 3581-3525-TIMKEN - 3581-3525-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/3581-3525-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Static <sup>(2)</sup> C <sub>0</sub>	Dynamic <sup>(3)</sup> C <sub>10</sub>	Static <sup>(4)</sup> C <sub>0</sub>	Factor <sup>(5)</sup> K	Inner	Outer		
mm	mm	mm	N	N	N	N					
34.925	87.312	30.162	113000	231	1.96	29000	15000	1.91	134000	2581	2525
1.3750	3.4375	1.1975	25500			6810	3468		30180		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
Width B	Width C	ER. Dr. μm	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	Max Housing Fillet Radius r <sub>2</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(6)</sup>				A <sub>2</sub> <sup>(7)</sup>	A <sub>3</sub> <sup>(8)</sup>
30.086	23.812	-18.2	3.5	43.8	48.5	3.3	81.0	75.0	2.2	8.7	35.5	12.5	0.0008	8.82
1.2160	0.9375	-0.40	0.14	1.69	1.95	0.13	3.19	2.95	0.09	0.03				2.00

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952311050
Diam. intérieur	34.93 mm
Diam. extérieur	87.31 mm
Épaisseur	30.16 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE