

## Roulement conique 2788A-2736-TIMKEN - 2788A-2736-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/2788a-2736-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number			
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(3)</sup> C <sub>02</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Inner	Outer			
mm	mm	mm	N		N		N					
38.130	74.612	23.812	8000	1.30	156		2500	11700	1.52	10200	2788A	2736
1.500	2.9375	0.9375	1950				560	2936		2300		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. μm	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				A <sub>3</sub> <sup>(1)</sup>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
23.812	19.950	-0.1	1.5	43.5	46.8	0.8	30.8	67.8	1.4	8.5	25.7	12.2	0.0725	6.48
0.9375	0.7500	-0.32	0.06	1.71	1.81	0.03	2.76	2.64	0.05	0.04				1.06

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952311760
Diam. intérieur	38.1 mm
Diam. extérieur	74.612 mm
Épaisseur	23.812 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE